

**Key Features**

Embedded Linux OS
 Triplex Function
 Watch dog/Power failure recovery
 IR Remote Controller
 E-mail notification: Alarm, Video loss, Power loss, HDD failure
 6-Level Password

**Specifications**

System Control	Key Buttons, IR Remote Control, Remote Client PC
Motion Detection/channel	16 Selectable grids, 20 Sensitivity levels
Communications Ports	RJ-45, Ethernet, RS-232C, RS-422, USB1.1
Format	NTSC
Compression	MPEG-4
Input	25 Pin Pigtail, 8 BNC
Output	Main and Spot monitor, VGA
Audio	4 Inputs
Display Resolution	120 pps/ 720x480
Recording Resolution	120pps/360x240, 120pps/720x240, 30pps/720x480
Average File size	2.5 ~ 8KB
Triplex functions	Simultaneous Record/Playback/Network or Backup
Recording Modes	Continuous, Schedule, Alarm, Motion, Overwrite
Hard Drive	250GB, 500GB, 750GB
Alarm Input	8 in 2 out
Trigger Mode	Motion Detection, Sensor Input
Recording Adjustments	5 Levels resolution/Recording FR per camera
Prealarm/Post Alarm recording	Pre 4 sec/Post 10sec~300sec
Search Method	Time&Date, camera, alarm, motion
Back-up Device	DVD-RW
Power Supply	100~230VAC(50~60Hz), Universal
Weight	3.9Kg, 8.6lbs
Dimensions	13.8"x9.85"x3.25"
Operating Temperature	14-104F