

B/W & COLOR DOOR VIEW CAMERA

KPC-S190DV & KPC-S190CDV (SONY 1/3" SUPER HAD CCD)



KPC-190DV



KPC-S190CDV

SPECIFICATIONS

MODEL	KPC-S190DV	KPC-S190CDV
	EIA	NTSC
Image Device	Sony 1/3" Super HAD CCD	
Total Pixels	537(H) x 505(V)	
Effective Pixels	510(H) x 492(V)	
H. Resolution	More than 420 TV Lines	380 TV Lines
Sensitivity	0.05 Lux / F2.0	0.5 Lux / F2.0
Scanning System	2:1 Interlace	
Sync. System	Internal	
S/N Ratio	More than 50dB	
Gamma Correction	$\gamma=0.45$	
Video Output	Composite 1 [V _{p-p}] 75(Ω) unbalanced	
Electronic Shutter	1/60 ~ 1/100,000 sec. Auto	
Current Consumption	100mA or less	
Power Supply	DC12V ($\pm 10\%$)	
Operating Temperature	-10°C ~ +50°C	
Storage Temperature	-30°C ~ +60°C	
Dimensions	19(mm) ϕ	
Lenses Options	M12 Wide Angle Lens 170°	

* ALL SPECS ARE SAME EXCEPT LENS TYPE

WIRING DIAGRAM



