

B/W CYLINDER CAMERA

KPC-S190S SERIES (SONY 1/3" SUPER HAD CCD)



KPC-S190SWX/KPC-S190SHWX
(WATER RESISTANT/ LENS EXCHANGEABLE)



KPC-S190SP1
(0.05LUX/F2.0, f3.7mm)



KPC-S190SP3
(0.05LUX/F2.0, f3.7mm)



KPC-S190SB1
(0.05LUX/F2.0, f3.6mm)



KPC-S190SP4
(0.05LUX/F2.0, f4.3mm)

SPECIFICATIONS			
MODEL	KPC-S190S		KPC-S190SHWX
	EIA		EIA
Image Device	SONY 1/3" SUPER HAD CCD		SONY 1/3" SUPER HAD CCD
Total Pixels	537(H) x 505(V)		811(H) x 508 (V)
Effective Pixels	510(H) x 492(V)		768(H) x 494(V)
H. Resolution	More than 420 TV Lines		600 TV Lines
Sensitivity	0.05 Lux / F2.0		0.1 Lux / F1.2
Signal System	60Hz		
Scanning System	2:1 Interlace		
Sync. System	Internal		
S/N Ratio	More than 50dB		
Gamma Correction	γ=0.45		
Video Output	Composite 1 [Vp-p] 75(Ω) unbalanced		
Electronic Shutter	1/60 ~ 1/100,000 sec. Auto		
Current Consumption	100mA or less		
Power Supply	DC12V (±10%)		
Operating Temperature	-10°C ~ +50°C		
Storage Temperature	-30°C ~ +60°C		
Dimensions	19(mm)φ		
Board Lens Mount	f3.6mm (Stand) - 92° (Diagonal)		
Pinhole Mount	F3.5	f3.7mm (Stand) - 90° (Diagonal)	
	F2.0	f3.7mm (Stand) - 90° (Diagonal)	
Connection	Refer to wiring diagram		
Lenses Options	Board lens: 2.45(Except Water Proof Cameras)/2.97/3.6/4.3/6.0/8.0/12(mm) Pinhole Lens: 3.7(90°)-F2.0, 4.3(78°)-F2.0 (Not available w/ WaterProof Housing)		

* ALL SPECS ARE SAME EXCEPT LENS TYPE

